

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

Claims 1-3 (canceled).

Claim 4 (withdrawn): A processor that executes instructions in threads, said processor comprising:

a context register file having a separate set of general registers for a plurality of contexts, wherein said threads are each assigned a separate context; and context control registers having a separate set of control registers for the plurality of contexts

Claim 5 (withdrawn): The processor of claim 4, wherein the context register file includes 32 general registers for 8 contexts.

Claim 6 (withdrawn): The processor of claim 4, wherein the context register file includes for each context:

a context program counter;
a context status register; and
a write address register.

Claim 7 (withdrawn): The processor of claim 6, wherein the context program counter holds a program counter pointing to a next instruction in an associated context.

Claim 8 (withdrawn): The processor of claim 6, wherein the context status register holds data that indicates whether an associated context is awaiting data from an external source.

Claim 9 (withdrawn): The processor of claim 6, wherein the write address register stores an address of a register associated with a context that is awaiting data.

Claim 10 (withdrawn): The processor of claim 6 further including:
a scheduler configured to select a context to activate.

Claim 11 (withdrawn): The processor of claim 10 further including:
means for receiving a context switch instruction;
means for receiving an identifier of a next context to activate from the scheduler;
means for performing a next instruction in a current context; and
means for pointing a processor program counter to the context program counter in the context control register associated with the next context.

Claim 12 (original): A processing system comprising:
a processor configured to
formulate an instruction and data, from a thread associated with a first context, for sending to a device, said instruction requesting the device to perform a command and return data to the processor;

perform a context switch to switch from processing the first context to a second context; and

a bus controller configured to

generate a system bus operation to send the formulated instruction and data along with a thread identifier to the device.

Claim 13 (original): The processing system of claim 12, wherein the processor is further configured to store an address of a destination register associated with the first context receiving the return data.

Claim 14 (original): The processing system of claim 13, wherein the bus controller is further configured to receive the device return data from a system bus along with the thread identifier.

Claim 15 (original): The processing system of claim 14, wherein said processor is configured to

write the return data to the stored destination register associated with the first context; and

clear a wait bit in a status register associated with the first context.

Claim 16 (original): The processing system of claim 12, wherein the device is a table lookup unit.

Claim 17 (original): The processing system of claim 12 said processor further including:

a context register file having a separate set of general registers for the first and second contexts; and

context control registers having a separate set of control registers for the first and second contexts.

Claim 18 (original): The processing system of claim 17, wherein the context register file includes 32 general registers for the each context.

Claim 19 (original): The processing system of claim 17, wherein the context register file includes for each context:

a context program counter;

a context status register; and

a write address register.

Claim 20 (original): The processing system of claim 19, wherein the context program counter holds a program counter pointing to a next instruction in an associated context.

Claim 21 (original): The processing system of claim 19, wherein the context status register holds data that indicates whether an associated context is awaiting data from an external source.

Claim 22 (original): The processing system of claim 19, wherein the write address register stores an address of a register associated with a context awaiting data.

Claim 23 (original): The processing system of claim 19 further including:
a scheduler configured to select the second context to activate.

Claim 24 (original): The processing system of claim 23 further including
means for receiving an identifier of the second context to activate from the scheduler;

means for performing a next instruction in the first context; and

means for pointing a processor program counter to the context program counter in the context control register associated with the second context.

Claim 25 (canceled).

Claim 26 (withdrawn): A method for switching between contexts using a processor having a context register file having a separate set of general registers for a plurality of contexts, each of registers associated with a thread, and context control

registers having a separate set of control registers for the plurality of contexts, said method comprising the steps of:

receiving a context switch instruction;

receiving an identifier of a next context to activate from the scheduler;

performing a next instruction in a current context; and

pointing a processor program counter to the context program counter in the context control register associated with the next context.

Claim 27 (new): A method comprising:


formulating, in a processor, an instruction and data from a thread associated with a first context for sending to a device, the formulated instruction requesting the device to perform a command and return data to the processor;

performing, in the processor, a context switch to switch from processing the first context to a second context; and

generating, in a bus controller, a system bus operation to send the formulated instruction and data along with a thread identifier to the device.

Claim 28 (new): The method of claim 27 further comprising storing an address of a destination register associated with the first context for receiving the return data.

Claim 29 (new): The method of claim 28 further comprising:
writing the return data to the destination register; and
clearing a wait bit in a status register associated with the first context.



Claim 30 (new): The method of claim 27 further comprising, in the device:
performing an operation in response to the formulated instruction and data; and
loading the return data resulting from the operation and thread identifier onto a
system bus.

Claim 31 (new): The method of claim 30 further comprising receiving the
return data and thread identifier in the bus controller.

Claim 32 (new): The method of claim 27 further comprising initiating the
system bus operation in the processor before performing the context switch.

Claim 33 (new): The method of claim 27 wherein performing the context
switch comprises:
receiving an identifier of the second context;
performing a next instruction in the first context; and
changing a program counter in the processor from a value associated with the first
context to a value associated with the second context.
